



HexWeb® Honeycomb

- for Motorsport and Performance Cars

This guide has been compiled to assist with the selection of the best type of honeycomb for a particular application. More detailed information is included in the individual product data sheets, available on request.

METALLIC

Product type	Strength	Stiffness	Max Service Temp °C	Thermal Conductivity/ Characteristics	Product Form	Density Range kg/m ³	Recommended Applications	Treatment Options	Environmental Resistance
					Density Range kg/m ³				
CR111 Spec Aerospace Grade Aluminium Honeycomb	High	High	175	High	Microcell	104 to 198	Air directionalisation	Chromated	Good
					Rigicell	168 to 880	High load areas		
					Flexcore	34 to 128			
ACG Commercial Grade Aluminium Honeycomb	High	High	175	High	Hexagonal cell	34 to 192	High performance structural + energy absorption	CR-PAA treated and primed	Excellent
					Hexagonal cell	29 to 83	Low performance structural	CRF (Chrome Free)	

NON-METALLIC

Product type	Strength	Stiffness	Max Service Temp °C	Thermal Conductivity/ Characteristics	Product Form	Density Range kg/m ³	Recommended Applications	Environmental Resistance	
					Density Range kg/m ³				
HRH-78 Commercial Grade Phenolic Dipped Aramid Core	High	Moderate	175	Low	Hexagonal cell	29 to 80	Structural	Excellent	
					OX cell	29 to 64			Single curvature
					Flexcore	40 to 88			Compound curvature
HRH-10 Aerospace Grade Phenolic Dipped Aramid Core	High	Moderate	175	Low	Hexagonal cell	28 to 96	Structural	Excellent	
					OX cell	Single curvature			
HRH-36 Aerospace Grade Phenolic Dipped Core	High	High	175	Low	Flexcore	Contact Hexcel	Compound curvature	Excellent	





HexWeb® Honeycomb

- for Motorsport and Performance Cars

For further information, please contact your nearest sales office, or visit our website at www.hexcel.com

Australia

Suite 2, 86 Grimshaw Street
Greensborough, Victoria 3088
Tel: **61 3 9432 7100**
Fax: **61 3 9432 7200**

Austria

Industriestrasse 1
A-4061, Pasching
Tel: **43 (0)7229 7720**
Fax: **43 (0)7229 772299**

Belgium

Rue Trois Bourdons, 54
B-4840 Welkenraedt
Tel: **32 87 307 411**
Fax: **32 87 882 895**

Brazil

Av. J. Guilhermino, 474/72
S.J.Campos, SP 12210-130
Tel: **55 12 3941 2242**
Fax: **55 12 3923 1186**

China

Room B707, Yin Hai Bldg.
250 Cao Xi Rd
Shanghai 200233
Tel: **86 21 6483 6741/2**
Fax: **86 21 6483 6744**

France

ZI La Plaine, B.P.27 Dagneux
01121 Montluel CEDEX
Tel: **33 (0)4 72 25 26 27**
Fax: **33 (0)4 72 25 27 30**

Germany

Postfach 1560
21655 Stade
Tel: **49 4141 7879-00**
Fax: **49 4141 7879-01**

Italy

Via San Cristoforo, 44
21047 Saronno (VA)
Tel: **39 02 96709082**
Fax: **39 02 9600809**

Japan - Joint Venture

DIC - Hexcel Limited
7F Nissei Bldg.
6-2-8 Sotokanda
Chiyoda-ku, Tokyo 101-0021
Tel: **81 3 5812 3361**
Fax: **81 3 3837 7522**

Spain

Bruselas, 10 - 16
Polig. Ind. "Ciudad de Parla"
28980 Parla, Madrid
Tel: **34 91 664 4900**
Fax: **34 91 698 4914**

United Kingdom

Duxford, Cambridgeshire
CB2 4QD
Tel: **44 (0)1223 833141**
Fax: **44 (0)1223 838808**

USA

900 Main Street South,
Building 1, Suite 104,
Southbury, CT 06488
Tel: **1 203 267 1414**
Fax: **1 203 267 1561**

USA

2350 Airport Freeway, Suite 550
Bedford, TX 76022-6027
Tel: **1 817 315 3939**
Fax: **1 817 571 8629**

USA

16310 NE 80th Street, Suite 102
Redmond, WA 98052
Tel: **1 425 558 4400**
Fax: **1 425 861 5847**

USA

11771 Dublin Blvd.
Dublin, CA 94568-2832
Tel: **1 925 551 4900**
Fax: **1 925 828 9202**

® Copyright Hexcel Corporation
Publication ATU 265a (March 2005)





Redux® Adhesives

- for Motorsport and Performance Cars

This guide has been compiled to assist with the selection of the best product for an adhesive application. More detailed information is included in the individual product data sheets, available on request.

Redux® Adhesive	Maximum Operating Temperature °C	Key Features	Cure Cycle		Associated Products		
			Time (minutes)	Temperature °C	Redux Primer	Redux Foaming Film	
Epoxy Film							
609	100	<ul style="list-style-type: none"> ● Cure cycle flexibility ● Suitable for a wide range of industrial bonding 	60	120	112	212 NA 206-NA High foaming ratio	
335	90	<ul style="list-style-type: none"> ● Outstanding peel performance ● Enhanced sub-zero properties ● Optimum co-cure with 120°C curing prepregs 	60	120	112	212-NA 206-NA High foaming ratio	
641	150 long periods 175 short periods	<ul style="list-style-type: none"> ● Excellent mechanical performance to 150°C ● High peel performance 	60	175	122	219/2-NA 219/3-NA Low exotherm for thicker sections	
BMI Film							
HP655	232	<ul style="list-style-type: none"> ● High fracture toughness ● High shear strength ● Good peel strength 	240	191 + post cure	655P		
Foaming Film							
206NA	100	<ul style="list-style-type: none"> ● High foaming ratio 	60	120	112		
212NA	100	<ul style="list-style-type: none"> ● Foaming film 	60	120	112		
219/2NA	175	<ul style="list-style-type: none"> ● Foaming film 	60	175	119, 122		
219/3NA	175	<ul style="list-style-type: none"> ● Foaming film ● Low exotherm for thick sections 	60	190	119, 122		





Redux® Adhesives

- for Motorsport and Performance Cars

For further information, please contact your nearest sales office, or visit our website at www.hexcel.com

Australia

Suite 2, 86 Grimshaw Street
Greensborough, Victoria 3088
Tel: **61 3 9432 7100**
Fax: **61 3 9432 7200**

Austria

Industriestrasse 1
A-4061, Pasching
Tel: **43 (0)7229 7720**
Fax: **43 (0)7229 772299**

Belgium

Rue Trois Bourdons, 54
B-4840 Welkenraedt
Tel: **32 87 307 411**
Fax: **32 87 882 895**

Brazil

Av. J. Guilhermino, 474/72
S.J.Campos, SP 12210-130
Tel: **55 12 3941 2242**
Fax: **55 12 3923 1186**

China

Room B707, Yin Hai Bldg.
250 Cao Xi Rd
Shanghai 200233
Tel: **86 21 6483 6741/2**
Fax: **86 21 6483 6744**

France

ZI La Plaine, B.P.27 Dagneux
01121 Montluel CEDEX
Tel: **33 (0)4 72 25 26 27**
Fax: **33 (0)4 72 25 27 30**

Germany

Postfach 1560
21655 Stade
Tel: **49 4141 7879-00**
Fax: **49 4141 7879-01**

Italy

Via San Cristoforo, 44
21047 Saronno (VA)
Tel: **39 02 96709082**
Fax: **39 02 9600809**

Japan - Joint Venture

DIC - Hexcel Limited
7F Nissei Bldg.
6-2-8 Sotokanda
Chiyoda-ku, Tokyo 101-0021
Tel: **81 3 5812 3361**
Fax: **81 3 3837 7522**

Spain

Bruselas, 10 - 16
Polig. Ind. "Ciudad de Parla"
28980 Parla, Madrid
Tel: **34 91 664 4900**
Fax: **34 91 698 4914**

United Kingdom

Duxford, Cambridgeshire
CB2 4QD
Tel: **44 (0)1223 833141**
Fax: **44 (0)1223 838808**

USA

900 Main Street South,
Building 1, Suite 104,
Southbury, CT 06488
Tel: **1 203 267 1414**
Fax: **1 203 267 1561**

USA

2350 Airport Freeway, Suite 550
Bedford, TX 76022-6027
Tel: **1 817 315 3939**
Fax: **1 817 571 8629**

USA

16310 NE 80th Street, Suite 102
Redmond, WA 98052
Tel: **1 425 558 4400**
Fax: **1 425 861 5847**

USA

11771 Dublin Blvd.
Dublin, CA 94568-2832
Tel: **1 925 551 4900**
Fax: **1 925 828 9202**





HexPly® Prepregs

- for Motorsport and Performance Cars

This guide has been compiled to assist with the selection of the best matrix for a prepreg application. More detailed information is included in the individual product data sheets, available on request.

HexPly® Resin Systems	Dry Tg Onset (DMA) °C (°F)	Typical Cure Cycle		Cure Process		Self Adhesive	Flow			Toughness			Self-Extinguishing	Outlife at Room Temp (days)	Storage at -18°C (0°F) (months)	Standard Prepreg Form		
		Temp °C (°F)	Time (mins)	Autoclave/ Press	Vacuum Only		Controlled	High	High	Med	Low	UD Tape				Fabric	Tow Preg	Split Tape

Epoxy

M10	125 (255)	120 (250)	60	X	X			X		X				60	12	X	X		
M35-4	135 (275)	135 (275)	90	X	X		X		X					60	12	X	X		
M47	145 (295)	135 (275)	90	X			X			X				30	12	X	X		
M48	201 (394)	180 (356)	120	X					X					30	12	X	X		
M49	120 (250)	120 (250)	90	X	X				X					30	12	X	X		

Phenolic

200	(200 (390) in service)	150 (300)	60	X			X			X				30	12		X		
-----	------------------------	-----------	----	---	--	--	---	--	--	---	--	--	--	----	----	--	---	--	--

BMI

F655	290 (550)	190 (375)	240 + PC	X			X			X				30	12	X	X		
------	-----------	-----------	----------	---	--	--	---	--	--	---	--	--	--	----	----	---	---	--	--





HexPly® Prepregs

- for Motorsport and Performance Cars

HexPly® Resin Systems	Benefits	Area of Use
Epoxy		
M10	<ul style="list-style-type: none"> ● Good outlife ● Easy processability 	<ul style="list-style-type: none"> ● Structural parts and components
M35-4	<ul style="list-style-type: none"> ● High toughness ● Excellent mechanical properties ● High temperature properties ● Flexible cure 	<ul style="list-style-type: none"> ● Bodywork and components/chassis
M47	<ul style="list-style-type: none"> ● Good toughness ● Excellent temperature properties ● Excellent surface finish 	<ul style="list-style-type: none"> ● Bodywork and components/chassis
M48	<ul style="list-style-type: none"> ● Outstanding toughness and damage tolerance at high temperatures 	<ul style="list-style-type: none"> ● Chassis and rear crash structure/High service temperature components
M49	<ul style="list-style-type: none"> ● High Toughness ● Excellent self adhesive properties on A1 honeycomb ● Excellent surface finish ● Vacuum bag processable 	<ul style="list-style-type: none"> ● Bodywork and components/chassis
Phenolic		
200	<ul style="list-style-type: none"> ● Ablative phenolic matrix for firewall protection 	<ul style="list-style-type: none"> ● Fire proof components
BMI		
F655	<ul style="list-style-type: none"> ● Superior toughness at very high service temperatures (up to 200°C) 	<ul style="list-style-type: none"> ● Specialist applications such as gearboxes

For further information, please contact your nearest sales office, or visit our website at www.hexcel.com

® Copyright Hexcel Corporation
Publication FTU 266a (March 2005)

Australia
Suite 2, 86 Grimshaw Street
Greensborough, Victoria 3088
Tel: **61 3 9432 7100**
Fax: **61 3 9432 7200**

Austria
Industriestrasse 1
A-4061, Pasching
Tel: **43 (0)7229 7720**
Fax: **43 (0)7229 772299**

Belgium
Rue Trois Bourdons, 54
B-4840 Welkenraedt
Tel: **32 87 307 411**
Fax: **32 87 882 895**

Brazil
Av. J. Guilhermino, 474/72
S.J.Campos, SP 12210-130
Tel: **55 12 3941 2242**
Fax: **55 12 3923 1186**

China
Room B707, Yin Hai Bldg.
250 Cao Xi Rd
Shanghai 200233
Tel: **86 21 6483 6741/2**
Fax: **86 21 6483 6744**

France
ZI La Plaine, B.P. 27 Dagneux
01121 Montluel CEDEX
Tel: **33 (0)4 72 25 26 27**
Fax: **33 (0)4 72 25 27 30**

Germany
Postfach 1560
21655 Stade
Tel: **49 41 41 7879-00**
Fax: **49 41 41 7879-01**

Italy
Via San Cristoforo, 44
21047 Saronno (VA)
Tel: **39 02 96709082**
Fax: **39 02 9600809**

Japan - Joint Venture
DIC - Hexcel Limited
7F Nissei Bldg.
6-2-8 Sotokanda
Chiyoda-ku, Tokyo 101-0021
Tel: **81 3 5812 3361**
Fax: **81 3 3837 7522**

Spain
Bruselas, 10 - 16
Polig. Ind. "Ciudad de Parla"
28980 Parla, Madrid
Tel: **34 91 664 4900**
Fax: **34 91 698 4914**

United Kingdom
Duxford, Cambridge
CB2 4QD
Tel: **44 (0)1223 833141**
Fax: **44 (0)1223 838808**

USA
900 Main Street South,
Building 1, Suite 104,
Southbury, CT 06488
Tel: **1 203 267 1414**
Fax: **1 203 267 1561**

USA
2350 Airport Freeway, Suite 550
Bedford, TX 76022-6027
Tel: **1 817 315 3939**
Fax: **1 817 571 8629**

USA
16310 NE 80th Street, Suite 102
Redmond, WA 98052
Tel: **1 425 558 4400**
Fax: **1 425 861 5847**

USA
11711 Dublin Blvd.
Dublin, CA 94568-2832
Tel: **1 925 551 4900**
Fax: **1 925 828 9202**





HexFlow® RTM Resins

- for Motorsport and Performance Cars

This guide has been compiled to assist with the selection of the best type of resin transfer moulding system for a particular application. More detailed information is included in the individual product data sheets, available on request.

Resin System	Max Service Temp. (dry) °C (°F)	Cure Cycle		Post Cure Time/Temp °C (°F)	Minimum Cure		Outlife at Room Temperature (days)	Outlife at -18°C (0°F) (months)
		Time	Temp °C (°F)		Pressure	Time		
Epoxy								
RTM 6	180 (350)	75 min	160 (320)	2 hours 180 (350)	75 min	160 (320)	15	9
BMI								
RTM 651	232 (450)	4 hours	191 (375)	85 psi 16 hours 232 (450) or 6 hours 245 (475)	4 hours	191 (375)	30	12

For further information, please contact your nearest sales office, or visit our website at www.hexcel.com

© Copyright Hexcel Corporation
Publication ITU 268a (March 2005)

Australia
Suite 2, 86 Grimshaw Street
Greensborough, Victoria 3088
Tel: 61 3 9432 7100
Fax: 61 3 9432 7200

Austria
Industriestrasse 1
A-4061, Pasching
Tel: 43 (0)7229 7720
Fax: 43 (0)7229 772299

Belgium
Rue Trois Bourdons, 54
B-4840 Welkenraedt
Tel: 32 87 307 411
Fax: 32 87 882 895

Brazil
Av. J. Guilhermino, 474/72
S.J.Campos, SP 12210-130
Tel: 55 12 3941 2242
Fax: 55 12 3923 1186

China
Room B707, Yin Hai Bldg.
250 Cao Xi Rd
Shanghai 200233
Tel: 86 21 6483 6741/2
Fax: 86 21 6483 6744

France
ZI La Plaine, B.P. 27 Dagneux
01121 Montluel CEDEX
Tel: 33 (0)4 72 25 26 27
Fax: 33 (0)4 72 25 27 30

Germany
Postfach 1560
21655 Stade
Tel: 49 41 41 7879-00
Fax: 49 41 41 7879-01

Italy
Via San Cristoforo, 44
21047 Saronno (VA)
Tel: 39 02 96709082
Fax: 39 02 9600809

Japan - Joint Venture
DIC - Hexcel Limited
7F Nissei Bldg.
6-2-8 Sotokanda
Chiyoda-ku, Tokyo 101-0021
Tel: 81 3 5812 3361
Fax: 81 3 3837 7522

Spain
Bruselas, 10 - 16
Polig. Ind. "Ciudad de Parla"
28980 Parla, Madrid
Tel: 34 91 664 4900
Fax: 34 91 698 4914

United Kingdom
Duxford, Cambridge
CB2 4QD
Tel: 44 (0)1223 833141
Fax: 44 (0)1223 838808

USA
900 Main Street South,
Building 1, Suite 104,
Southbury, CT 06488
Tel: 1 203 267 1414
Fax: 1 203 267 1561

USA
2350 Airport Freeway, Suite 550
Bedford, TX 76022-6027
Tel: 1 817 315 3939
Fax: 1 817 571 8629

USA
16310 NE 80th Street, Suite 102
Redmond, WA 98052
Tel: 1 425 558 4400
Fax: 1 425 861 5847

USA
11711 Dublin Blvd.
Dublin, CA 94568-2832
Tel: 1 925 551 4900
Fax: 1 925 828 9202

